



NYLON

PRETREATMENT

CODE	PRODUCT NAME	APPLICATION	DESCRIPTION
V043	OJAS - PSX LIQ.	Scouring Agent	Scouring cum wetting agent with excellent emulsifying - degreasing properties. DOSAGE: Exhaustion: 0.5 - 1.0 gpl, Padding: 3 - 5 gpl
V044	OJAS - PA	Antioxidant	Used to protect the fibre against damage during peroxide bleaching of cotton/polyamide blends. DOSAGE: Exhaustion: 0.5 - 1.0 gpl, Padding: 3 - 5 gpl

DYEING

CODE	PRODUCT NAME	APPLICATION	DESCRIPTION
V045	OJAS - ABN Anionic	Buffer cum dispersant	Acid buffer with dispersing, chelating properties. Use with levelling agent. DOSAGE: Exhaust : 0.5 - 2.0 gpl, Padding: 2.0 - 5.0 gpl
V046	OJAS - JQB Anionic	Levelling agent for acid dyes	Excellent levelling agent for acid dyes. Good levelling & migrating properties. DOSAGE: Exhaust: 0.5 - 2.0 gpl, Padding: 2.0 - 5.0 gpl
V047	OJAS - SMK Nonionic	Levelling agent	Suitable for nylon & its blend in metal - complex dyes. Can improve dye retarding property. DOSAGE: Exhaust: 0.5 - 2.0 gpl, Padding: 2.0 - 5.0 gpl
V048	OJAS - DFN Anionic	Fixing agent	Suitable for fixing treatment of acid dyes. Can improve light fastness. DOSAGE: Exhaust: 0.5 - 2.0 gpl, Padding: 3.0 - 5.0 gpl
V049	OJAS - EL Cationic	Soaping agent	Suitable as soaping agent for nylon dyeing. DOSAGE: Exhaust : 1.0 - 2.0 gpl